

High compression technology

Company

International Coverage

Alliances

Contact Us



PRODUCTS



Compressor



Storage



Control Panel



Dispensers



Gas Mobile Pipeline



CNG Mobile Station

APPLICATIONS



Gas Gathering



Gas Recovery Plants



Gas Plant Compressors



Landfill Gas



Gas Turbine Fuel Booster

Agıra

OUR COMPANY

Agira is a leader company in technology applied to Natural Gas compression. From its manufacturing plants in Argentina and United States produces all the products it sells worldwide. The Agira technology stands out for its unique robust design of all its products that increases the performance in a long term with minimum maintenance.

Since its inception, **Agira** constantly is searching for new challenges in different parts of the world where we can check the performance of our technology in the most varied conditions of use.

Agira is ethical committed to excellence, giving its support of ISO 9001-2008 certifications, in production, purchasing, sales & management standards; meeting the standards of Bureau Veritas International, UKAS& CE

Through the pursuit of total quality in all of its processes and the challenge of continuous improvement, **Agira** has been recognized with the **Export-Ar** Foundation Award **2008** in **"Consolidation of International Markets"** category and in **2009 edition** with the **"Opening New Markets"** category.



OUR FACTORIES







Erie, PA, USA





OUR MAIN MARKETS

- Venezuela
- Bolivia
- Brazil
- Chile
- USA
- Spain
- Armenia
- Georgia
- Iran

- Russia
- México
- Indonesia
- India
- Nigeria
- Bangladesh
- Turkey
- Colombia
- Trinidad & Tobago

COMPRESSORS

ELECTRIC DRIVEN

GAS ENGINE DRIVEN

MAIN CHARACTERÍSTICS

- •Reciprocating compressors.
- ·Simple and compac design
- •Inlet pressure from 5 psi
- •Power from 30 to 1500 HP
- ·Lub and non lub rings (optional)
- No vibration system
- Air cooling system
- Low maintenance cost



Ruta Panamericana Km.30 Colectora Oeste 30048 (1617) Pacheco, Buenos Aires, Argentina Tel: (5411) 6334-0000 sales@agira.com.ar

www.agira.com.ar



AGIRA KW 245



GENERAL CHARACTERISTICS

- Compressor Knox Western
- oSimple and compact design
- oType: Horizontally Opposed
- OAir cooling system
- oRemote PLC and electric control panel
- oDispatch temperature +2°Cof environment temperature.
- oUnique StopNoise® system No vibration
- Direct coupling or pulley

OPTIONAL

-Lubricated / non lubricated rings

Acoustic Canopy

MODELS

2 stages


3 stages

4 stages





AGIRA EAGLE COMPRESSORS



High Flow Compressors





Ruta Panamericana Km.30 Colectora Oeste 30048 (1617) Pacheco, Buenos Aires, Argentina Tel: (5411) 6334-0000 sales@agira.com.ar

www.agira.com.ar



AGIRA KW EAGLE



GENERAL CHARACTERISTICS

- High How Compressor
- OCompressor Knox Western
- 4 Throw compresor
- OSimple and compact design
- Type: Horizontally Oppossed
- OAir colling system
- o Remote PLC and electric control panel
- ODispach temperature +2°C of environment temperature.
- oUnique stopNoise system No vibration
- Direct coupling or pulley

MODELOS

3 stages

4 stages

5 stages

OPTIONAL

-Lubricated / non lubricated rings

- Acoustic Canopy





Gas Engine

AGIRA KW





GENERAL CHARACTERISTICS

oCompressor Knox Western

- oPackaged with Cummins/Caterpillar engines
- oSimple & compact design.
- Air cooling system
- oElectic panel and remote PLC.
- oDispatch temperature +2°C of enviroment temperature. .
- OAverage consumption of 0,05 m3 every m3 sold.
- oWater radiator incorporated in the machine
- oPneumatic starter
- oVariable speed according to demand.
- o **StopNoise**[®] System No vibration
- Direct coupling
- **oLubricated rings**

OPTIONAL

Acoustic Canopy





Gas Engine

AGIRA KW EAGLE





- o. High Flow Compressor
- OCompressor Knox Western
- o4 Throw compressor
- oPackaged with Cummins/ Caterpillar engines
- oSimple & compact design.
- Air cooling system
- o Hectric panel and remote PLC.
- ODispatch temperature +2°C of environment temperature.
- StopNoise* System No vibration
- oDirect coupling.
- oLubricated rings.

OPTIONAL

Acoustic Canopy





Gas Engine

AGIRA MILENIUM



GENERAL CHARACTERISTICS

- Compressor
- oPackaged with Caterpillar/Cummins gas engine
- Simple & compact design.
- Air cooling system
- o Electric panel and remote PLC.
- o Dispatch temperature +2°C of enviroment temperature.
- o Consumption: 0,05 m3 every m3 sold.
- oWater radiator incorporated in the machine
- o Pneumatic starter
- Variable speed according demand
- StopNoise System-No vibration
- Oirect coupling
- oLubricated rings

OPTIONAL



Ruta Panamericana Km.30 Colectora Oeste 30048 (1617) Pacheco, Buenos Aires, Argentina Tel: (5411) 6334-0000 sales@agira.com.ar



2 Stages

3 stages

4 stages

5 stages

Acoustic Canopy

Compressors

AGIRA BIG BULL



GENERAL CHARACTERISTICS

- oCompressor Knox Western
- OVariable suction pressures.
- oFlow capacity untill 300 Nm3/h.
- oWith or without 500lts storage included.
- ODispenser or Filling Post incorporated or remote (1 or 2 hoses).
- ODischarge pressure of 250 Bar.
- oHorizontal opposed cylinders
- oPower untill 60 HP(380/440 V 50/60).
- OAir cooling system.
- oMinumum space requirement.
- oMinimum maintenance cost.
- **oLubricated rings**
- OAcoustic canopy.



Ruta Panamericana Km.30 Colectora Oeste 30048 (1617) Pacheco, Buenos Aires, Argentina Tel: (5411) 6334-0000 sales@agira.com ar

View More Details

Compressors

AGIRA BIG BULL



Weight: 3600 KG



Ruta Panamericana Km.30 Colectora Oeste 30048 (1617) Pacheco, Buenos Aires, Argentina Tel: (5411) 6334-0000 sales@agira.com.ar

www.agira.com.ar

Equipment specially designed for low flows

The ideal choice for following works:

- ✓ Car & buses captive fleets.
- √ Forklift fleets, etc.
- ✓ Small locations wirthlow sales



STORAGE



GENERAL CHARACTERISTICS

- o Capacity: 1.250 Its. (STD) & additional according to requirements.
- oLoading priority valve.
- Out-off valve due to excess flow.
- oPressure indicator gauge 0-400 bar.
- oManual vent valve.
- oPressure relief valve 300 bar.
- Security Shut off pressure switch 275 bar (optional).







DISPENSERS



GENERAL CHARACTERISTICS

- o Compact design manufactured in stainless-steel
- oSimple or double hose.
- Last generation mother board
- ODesign system for high flow.
- o1o3 lines.
- o Mass flow meters of 30/80 kg/minute
- o Communication interfase RS485
- o "Breakaway" system, automatic hose uncoupling.
- Sound indication when load finish.
- o Loading temperature control, optional.
- Pre-testing load

1 10 10 10



GAS MOBILE PIPELINE

The solution to transport Natural Gas outside the net.





Ruta Panamericana Km.30 Colectora Oeste 30048 (1617) Pacheco, Buenos Aires, Argentina Tel: (5411) 6334-0000 sales@agira.com.ar

next







System Components





MOTHER STATION

This is a refuelling station suitable to load the Mobile Gas Pipeline fast and efficient.

The gas is obtain from the gas pipeline.

This station can be used simultaneously to load vehicles, buses and Mobile Pipeline.




View Larger Image












back



SATELLITE SYSTEM

It consists of a service station that feeds variable Mobile Pipeline pressure between 200 and 15 Bar

Gas is extracted from Mobile Pipeline and compressed to keep always constant pressure at dispersers




View Larger Image



Ruta Panamericana Km.30 Colectora Oeste 30048 (1617) Pacheco, Buenos Aires, Argentina Tel: (5411) 6334-0000 sales@agira.com.ar

www.agira.com.ar









TRAILER

- Semitrailer type
- oMaximum storage pressure: 250 Bar
- OHydraulic capacity 21.000 Lts.
- oLoading capacity: 6.300 m
- oWeight: Net 33.640 Kg.
- oLoad 4.338 Kg.
- o Total gross weight 37.938 Kg.
- **Oimensions**:
 - •Width 2,60 mts
 - ·Long 9 mts
 - •Height 3,35 mts









sales@agira.com.ar



























REFUELLING STATIONS







REFUELLING STATIONS







ISTANBUL BUSES STATION







High Flow Compressors, Flow of 10.000 m3/h, 250 Buses Daily







OTHER APLICATIONS





Gas Gathering

Compressors are used in gas gathering applications for compressing natural gas produced from individual wells and other sources. The gas is stored or gathered through a network of pipelines and travels through a central pipeline to a designated location. Natural Gas produced from individual wells is gathered and compressed. The Natural Gas may be gathered from several different sources, such as a gas well, an associated gas and casing head gas, produced from an individual oil well, or gathered from other production facilities.



2-Throw 2-Stages 400hp



Offshore Plattaform





Gas Recovery Plants

The reciprocating compressor is an integral part of purification and recovery systems used in many plants to prevent venting or burning valuable gases after being used in industrial processes. These compressors are integrated into the systems to ensure proper pressurization and temperature control of the feed, waste, and product gases














Gas Plant Compressors

A gas plant is an operation designed to remove heavier, more valuable components from the methane in a gas stream. During this process a pressure drop is required, which must be recovered prior to introducing the gas into the pipeline. For small plants, this is usually a gas engine driven compressor.









4-Throw 4-Stages 400hp

Tel: (5411) 6334-0000

sales@agira.com.ar

Ruta Panamericana Km.30 Colectora Oeste 30048 (1617) Pacheco, Buenos Aires, Argentina

Landfill Gas

Landfill gas is generated when organic wastes in a municipal solid waste landfill decompose. The gas consists of about 50% methane (CH₄), the primary component of natural gas, about 50% of carbon dioxide (CO₂), and a small amount of non-methane organic compounds. Once produced, the gas can be collected by drilling a series of wells into the landfill and connected by a piping system network. The gas is then gathered and compressed for use in producing electricity





Gas Turbine Fuel Booster

The fuel gas booster is used to supply a constant amount of natural gas at a specific pressure to turbine-generators. The pressure available from many supply sources is insufficient for the demands of the turbine, therefore a compressor is required. Control devices to ensure that the correct capacity is maintained as inlet conditions fluctuate are a very important component of the compressor system.











www.agira.com.ar

www.agira.com.ar